

SALICE



Benchmark
Salice Pocket Door – Hawa Concepta

SALICE

Technical features

Max Load	66 lbs (30 kg)
Door Width	15-3/4" - 35-7/16" (400-900mm)
Door Height	61-1/32" – 98-7/16" (1550-2500mm*)
Door Thickness	3/4" – 1-3/16" (19-30 mm)
Inset door application	Yes
Opening and closing decelerated system	Yes
Min Cabinet depth	15-3/4" (400 mm)

SALICE

Technical features

Vertical door Adjustment	+4, -1
Horizontal door adjustment	± 2
Easy to remove from the cabinet	Yes

SALICE

Key Advantages

Pre-assembled without extra cost

Slide in and pull out assisted movements

Easy and quick mechanism pull out

High resistance and durability, certified with 100,000 cycles stress test

Decelerated door slide in

Quick frontal adjustable

Simple and fast assembly of the door from vertical bar

SALICE

Competition benchmark

	<u>Salice</u>	<u>Hawa</u>
Product model	Pocket Door	Concepta25/30
Door max weight	30Kg 67 lbs	25/30Kg 55/67 lbs
Door width	400-900 mm 15-3/4"-35-7/16"	300-900 mm 11-13/16"-35-7/16"
Door height	1500-2500 mm 61-1/32"-98-7/16"	1250-2500 mm 49-3/16"-98-7/16"
Door thickness	19-30 mm 3/4"-1 - 3/16"	19-30 mm 3/4"-1 - 3/16"
Mechanism space required	55 mm 2-3/16"	55mm 2-3/16"

SALICE

	<u>Salice</u>	<u>Hawa</u>
Product model	Pocket Door	Concepta25/30
Mechanism rear space required	107 mm 4-3/16"	73 mm 2-7/8"
Assisted door pull out	Yes	No
Assisted door slide in	Yes	No
Decelerated door slide in	Yes	No
Door frontal adjustment	Yes	Yes

SALICE

Salice

Hawa

Product model	Pocket Door	Concepta25/30
Quick disassembled process	Yes	No
Reversible mechanism left/right	No	Yes
Inset application	Yes	Yes

SALICE

