



Manufactured By
Arturo Salice S.p.A.
Como, Italy
www.saliceamerica.com

General Description

Grade 2, soft close concealed cabinet and furniture hinge for face frame cabinet design.
With an opening angle of 106 degrees.
Nickel or Titanium plated.
Corrosion resistant. Self-lubricating.
Cam adjustable

Applications

Suitable for commercial and institutional case work, office furniture and residential cabinetry where face frame construction is utilized.
Ideal for thicker doors up to 7/8". (22mm)
Ideal for doors with profile edge designs
Available for multiple overlays from 1/2" to 1-3/8".
Maximum door thickness: 7/8" (22mm)
Minimum door thickness: 9/16" (14mm)
Hinge cup depth: 7/16" (11mm)

Certifications: ANSI/BHMA, ISO9001, ISO14001

ANSI/BHMA

A.156.9-944.2
Sections: 4.2 Hinge set test.
Sections: 4.3 Operating life cycle
Sections: 4.4 Closing and extension

www.buildershardware.com
www.ansi.org



ARCAT Specification

Section 06 41 20
Cabinet/Drawer Hardware
www.arcat.com



ISO9001



www.iso.org/home.html

ISO14001



www.iso.org/home.html

Environmental Responsibility



Arturo Salice S.p.A. continually takes steps to insure our activities result in a positive impact on the environment. All Salice products exceed all international standards for environmental responsibility in the manufacturing process. This includes full compliance with **RoHS** certification. www.rohsguide.com

Buy American Act




Salice America meets all requirements to be in compliance with the Buy American Act. Title 41 U.S.C. §§ 8301-8305. www.fas.org/sgp/crs/misc/R43140.pdf

Consumer Product Safety Improvement Act 2008



All products manufactured by Arturo Salice S.P.A. are in compliance with consumer safety for lead content persuant to CPSIA Title 1 Section 101. www.cpsc.gov/Regulations

The Movement




Number of Hinges Specification

2 hinges: Doors up to 36 inches high, up to 24 inches wide, 20 lbs or less.
3 hinges: Doors up to 60 inches high, up to 24 inches wide, 40 lbs or less.
4 hinges: Doors up to 84 inches high, up to 24 inches wide, 60 lbs or less.
5 hinges: Doors up to 96 inches high, up to 24 inches wide, 80 lbs or less.

* Please contact Salice America for doors beyond these size and weight specifications.

Boring Pattern



Item Codes

CU_37D9 1/2" overlay, soft close, nickel plate
CU_36D9 9/16" overlay, soft close, nickel plate
CU_35D9 5/8" overlay, soft close, nickel plate
CU_34D9 3/4" overlay, soft close, nickel plate
CU_32D9 1" overlay, soft close, nickel plate
CU_3AD9 1-1/4" overlay, soft close, nickel plate
CU_3BD9 1-5/16" overlay, soft close, nickel plate
CU_3CD9 1-3/8" overlay, soft close, nickel plate

For Titanium plate, replace the last two digits (99) with (66)
Space " " in the part # indicates fixing type. Screw or dowel.

Industry Affiliations

Salice America actively participates with the top industry associations to maintain the highest possible quality assurance standards for the industry. Some industry partners include:

National Kitchen & Bath Association
www.nkba.org

Kitchen Cabinet Manufacturers Association
www.kcma.org

North American Building Materials Distribution Association
www.nbmda.org/p/ca/vi/sid=28

Architectural Woodworking Institute
www.awinnet.org

Woodwork Institute
www.woodworkinstitute.com

Cabinet Makers Association
www.cabinetmakers.org